

Classic Mystique PUR

PRODUCT SPECIFICATION

Key Features

- > Tonal non-directional heavy-duty homogeneous flooring
- > Broad palette of stylish colours
- > 100% recyclable & 25% recycled content
- > Low cost, polish-free maintenance
- > Healthcare & education interiors



Product Format	Standard	Result		
Gauge	ISO 24346 (EN 428)	2.0mm		
Total Weight	ISO 23997 (EN 430)	3250g/m ²		
Finish		PUR		

Sheet & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	24	-	40m ²
Tile	300mm x 300mm ■	8	50	4.5m ²
	608mm x 608mm +	8	14	5.17m ²

Performance Requirements	Standard	Result		
General Performance	ISO 10581	Conforms		
	ASTM F1913	Conforms		
	ASTM F1700	Class I, Type A		
Use Area	ISO 10874 (EN 685)	23, 34, 43		
Slip Resistance	EN 13893	Class DS		
	DIN 51130 / DIN EN 16165 Ann. B	R9		
	AS 4586	R9		
	ASTM D2047	SCOF ≥0.6		
Binder Content	ISO 10581	Type I		
Reaction to Fire	EN 13501-1	Class Bfl-S1		
	ASTM E648	Class 1		
	ASTM E662	<450		
	CAN/ULC S102.2	FSV < 300; SDV < 500		
	BCA Spec C1.10 Clause 3	Complies		
	AS ISO 9239-1	>8.0 kW/m ²		
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'		
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750psi)		
	ISO 24343-1	≤0.10mm		
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable		
Flexibility	ASTM F137	Pass		
Underfloor Heating		Suitable, max 27°C		

Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 472
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		25%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
VOC Emissions	TVOC after 28 days	≤ 10µg/m ³
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance

	Standard	Result
Impact Sound Reduction	ISO 10140-3	4dB

Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection. Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.

Hygiene

	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth
Ease of Radioactive Decontamination	ISO 8690	Excellent



Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Classic Mystique PUR



RANGE SHADES




Silent Dove 1540 w/r 1540
NCS S 1002-Y LRV 66




Quartz 1400 w/r 9340
NCS S 2500-N LRV 50
■ +




Pale Slate 1200 w/r 1200
NCS S 3502-B LRV 47
■ +



Steel Parade 1550 w/r 1550
NCS S 3500-N LRV 36



Smokestone 1160 w/r 9120
NCS S 4502-G LRV 28
■ +




Nocturne 1380 w/r 8270
NCS S 6502-B LRV 13
■ +




Atlantic Surf 1590 w/r 1590
NCS S 1510-R80B LRV 58



Ladoga 1410 w/r 1410
NCS S 2010-R90B LRV 46




Cloudburst 1210 w/r 1210
NCS S 2040-R90B LRV 32
■ +



Mountain Lake 1330 w/r 8350
NCS S 3020-R90B LRV 28
■ +



Delta Blue 1220 w/r 1220
NCS S 6020-R80B LRV 11



Lemon Zest 1140 w/r 1140
NCS S 1060-Y10R LRV 58



Silver Mist 1430 w/r 1430
NCS S 1505-Y40R LRV 62



Soft Almond 1560 w/r 1560
NCS S 1505-Y40R LRV 64



Satinwood 1370 w/r 8320
NCS S 1505-Y30R LRV 55
■ +




Shoreline 1460 w/r 1460
NCS S 2020-Y30R LRV 55
■ +



Nut Husk 1570 w/r 1570
NCS S 3005-Y50R LRV 38




Sorrel Bay 1580 w/r 1580
NCS S 3010-Y30R LRV 36




Cloud Stone 1530 w/r 1530
NCS S 4502-Y LRV 25




Smoked Truffle 1190 w/r 1190
NCS S 7005-Y20R LRV 12



Asparagus 1320 w/r 8360
NCS S 3010-G50Y LRV 37



Spring Meadow 1150 w/r 1150
NCS S 3050-G40Y LRV 22



Rich Chocolate 1520 w/r 1520
NCS S 7010-Y50R LRV 10



Sunblaze 1260 w/r 1260
NCS S 3060-Y90R LRV 14

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

■ Tile: 2.0mm - 300mm x 300mm

■ Tile: 2.0mm - 608mm x 608mm

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.