

POLYFLOR™
COVERING THE WORLD



homogeneous pur flooring





For attractive, high performance, homogeneous floorcoverings, the Polyflor PUR range of products is the perfect choice.

From traditional marbleised through to sophisticated non-directional decorations, including the unique multi-flake decoration of Pearlazzo, the PUR family of products offers excellent durability, reliability, ease of maintenance and endless design possibilities.

Realising the importance of colour and design in creating the perfect environment, Polyflor now invites you to explore the extensive colour options and combinations available to create truly inspirational interiors with enhanced maintenance protection.

Polyflor Homogeneous PUR - polyurethane reinforcement cross linked and UV cured - facilitates a lifelong polish-free maintenance regime, leading to overall maintenance cost savings of 48% over a 20 plus year life when compared to untreated homogeneous vinyl flooring. In addition, fewer cleaning chemicals and greatly reduced power requirements mean reduced environmental impact.

Positive environmental credentials and benefits are built into our flooring and there can be few materials better suited to recycling than vinyl flooring. Homogeneous PUR ranges are 100% recyclable and contain 25% recycled material.

There are many international schemes which assist specification of environmentally sound building materials - including BRE Global, EN 15804 EPD, FloorScore®, LEED®, and Green Tag. Polyflor Homogeneous PUR ranges are all approved products with these schemes, providing architects, planners and specifiers with an easier and effective way to select a more sustainable product.

Ideally suited for busy healthcare and education applications, as well as a wide variety of commercial environments, the Polyflor Homogeneous PUR range of polish-free flooring combines toughness, low maintenance and great style for the most demanding of areas.

For superior cleaning benefits, enhanced protection and optimum appearance retention, look no further than Polyflor Homogeneous PUR.

4
Pearlazzo PUR

8
Prestige PUR

12
Classic Mystique PUR

16
Mystique PUR

20
2000 PUR

24
Floorcare

25
Environment

26
Technical Specifications

LRV Publication in the Building Regulations, 2004, of 'Access to and use of Buildings' has made Light Reflectance Values (LRV) a key standard for designers, manufacturers and building owners. The values, tested in accordance with BS 8300:2009 are indicated at the top right of each Polyflor colour swatch.

NCS Natural Colour System®
The international language of colour favoured by paint companies, designers, architects and manufacturers. The closest perceived NCS references are shown at the bottom right of each Polyflor colour swatch.

polish free flooring



Pearlazzo PUR

Pearlazzo PUR enables you to bring a special brand of style and elegance to any commercial environment.

Available in a palette of 24 contemporary colours, ranging from pale neutrals through to more intense shades, Pearlazzo PUR features a unique multi-flake decoration giving it a distinct appeal.


As with all Homogeneous PUR ranges, Pearlazzo PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost polish-free maintenance regime for the lifetime of the flooring.

Polyflor Homogeneous PUR ranges demonstrate outstanding durability and abrasion resistance. Pearlazzo PUR achieves the highest abrasion wear rating Group T (EN 660 Part 2) and EN ISO 10581 Type I.


Following an individual assessment from BRE Global, Pearlazzo PUR achieves an A+ rating in major sectors such as health, education and retail (ENP 472).

Pearlazzo PUR is 100% recyclable and contains 25% recycled material.

Ideally suited for heavy traffic areas, Pearlazzo PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.



9717
Autumn Fire



9703
Chalk Burst



9716
Toasted Almond


distinctive flooring

Pearlazzo PUR


Blend of tonal chips and four pearlescent flakes

Key Features

- Attractive, high performance, heavy duty homogeneous floorcovering
- BRE Global environment A+ rating (Certificate No ENP 472)
- Achieves highest abrasion wear rating Group T tested to EN 660 Part 2, as defined in EN 649, EN ISO 10581 Type I
- Polyurethane reinforcement to facilitate a low-cost, lifetime polish-free maintenance regime
- Unique decoration comprising a blend of tonal chips and 4 pearlescent flakes, available in sheet
- Use Area Classification 23/34/43 as defined in EN685



9706 Mint Crisp 44.5




w/r 9706 NCS S 2020-B50G

9710 Seafoam 43.2




w/r 9710 NCS S 2020-B10G

9716 Toasted Almond 50.6




w/r 9716 NCS S 2005-Y30R

9701 Wild Flax 56.3




w/r 9701 NCS S 2010-G90Y

9707 Satin Jade 20.8



w/r 9707 NCS S 5020-B70G

9708 Alpine Meadow 40.0



w/r 9708 NCS S 3020-G30Y

9702 Lemon Ice 54.5




w/r 9702 NCS S 1515-Y10R


9718 Rain Cloud 34.2



w/r 9718 NCS S 3502-G




9720 Ocean Ripple 13.1




w/r 9720 NCS S 5030-B

9711 Atlantic Mist 25.7




w/r 9711 NCS S 3030-R90B

9709 Skylight 43.1



w/r 9709 NCS S 2010-R90B

9704 Mineral 43.2




w/r 9704 NCS S 2502-B

9721 Sunrise 47.6




w/r 3580 NCS S 2040-Y10R

9712 Sandcastle 46.6




w/r 9712 NCS S 2010-Y40R

9723 Caramel 39.3




w/r 9723 NCS S 3010-Y20R

9703 Chalk Burst 63.5




w/r 9703 NCS S 1502-Y

9705 Charcoal 9.8




w/r 4900 NCS S 7502-B

9715 Lilac Bloom 30.2




w/r 9715 NCS S 3020-R70B

9722 Purple Crush 14.2




w/r 9722 NCS S 5030-R70B

9725 Dark Berry 12.4




w/r 9725 NCS S 4040-R

9717 Autumn Fire 24.1




w/r 9717 NCS S 2060-Y60R

9713 Truffle 32.2




w/r 9713 NCS S 3020-Y40R

9724 Wholemeal 30.8




w/r 9724 NCS S 4005-Y20R

9719 Sailcloth 50.5



w/r 9719 NCS S 2002-Y50R

Please note: due to the limitations of printing, actual samples should be seen before colour selection is made. LRV Light Reflectance Value



Prestige PUR

Prestige PUR enables the creation of visually stunning installations, whatever the environment.

Available in 16 clean, attractive shades, Prestige PUR features a sophisticated non-directional decoration, with duotone base chips and tonal highlight chips. This co-ordinated palette allows for the easy combination of shades within a floor scheme.

As with all Homogeneous PUR ranges, Prestige PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost polish-free maintenance regime for the lifetime of the flooring.

Polyflor Homogeneous PUR ranges demonstrate outstanding durability and abrasion resistance. Prestige PUR achieves the highest abrasion wear rating Group T (EN 660 Part 2) and EN ISO 10581 Type I, demonstrating excellent resilience and long life.


Following an individual assessment from BRE Global, Prestige PUR achieves an A+ rating in major sectors such as health, education and retail (ENP 472).

Prestige PUR is 100% recyclable and contains 25% recycled material.


Ideally suited for heavy traffic areas, Prestige PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.




1910
Nutmeg



1860
Gingerlily



1960
Chilli



1600
Alabaster




a co-ordinated approach

Prestige PUR


Duotone chip decoration with tonal highlight chips

Key Features

- Attractive, high performance, heavy duty homogeneous floorcovering
- BRE Global environment A+ rating (Certificate No ENP 472)
- Achieves highest abrasion wear rating Group T tested to EN 660 Part 2, as defined in EN 649, EN ISO 10581 Type I
- Polyurethane reinforcement to facilitate a low-cost, lifetime polish-free maintenance regime
- Sophisticated non-directional decoration with duotone base chips and tonal highlight chips available in both sheet and tile
- Use Area Classification 23/34/43 as defined in EN685




1840 Stone Blue 28.9




w/r 1840 NCS S 4010-R90B

1800 Pale Iris 38.6




w/r 1800 NCS S 2020-R90B

1900 Bilberry 25.1




w/r 1900 NCS S 3040-R90B


1940 Liquorice 11.8



w/r 1940 NCS S 6500-N




1910 Nutmeg 58.2




w/r 1910 NCS S 1510-Y50R

1850 Cinnamon 48.7




w/r 1850 NCS S 1510-Y70R

1890 Thyme 52.9




w/r 1890 NCS S 1020-G40Y

1860 Gingerlily 63.7




w/r 1860 NCS S 2020-Y60R

1920 Lavender Mist 51.6




w/r 1920 NCS S 2020-R40B

1870 Peppermint 56.2




w/r 1870 NCS S 2020-B30G

1880 Chive 48.3




w/r 1880 NCS S 2010-G20Y

1960 Chilli 44.8




w/r 1960 NCS S 3040-Y70R

1830 Clove 32.6




w/r 1830 NCS S 4502-B

1930 Grey Marl 38.2




w/r 1930 NCS S 3502-R

1950 Ice Crystal 53.2



w/r 1950 NCS S 2002-R50B

1600 Alabaster 56.7



w/r 0630 NCS S 2005-Y10R

Please note: due to the limitations of printing, actual samples should be seen before colour selection is made. LRV Light Reflectance Value

Classic Mystique PUR

Classic Mystique PUR retains the uncomplicated, clean architectural feel of subtle neutrals, but now with added warmer tones for a perfectly balanced combination.

Available in 16 harmonious colours, Classic Mystique PUR has a tonal non-directional appearance, featuring a duotone chip decoration with marbled tonal highlight chips.

As with all Homogeneous PUR ranges, Classic Mystique PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost polish-free maintenance regime for the lifetime of the flooring.



Polyflor Homogeneous PUR ranges demonstrate outstanding durability and abrasion resistance.

Classic Mystique PUR achieves the abrasion wear rating EN ISO 10581 Type I, demonstrating excellent resilience and long life.

Following an individual assessment from BRE Global, Classic Mystique PUR achieves an A+ rating in major sectors such as health, education and retail (ENP 472).

Classic Mystique PUR is 100% recyclable and contains 25% recycled material.

Ideally suited for heavy traffic areas, Classic Mystique PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.




a balanced combination

Classic Mystique PUR


Duotone chip decoration with marbled tonal highlight chips

Key Features

- Attractive, high performance, heavy duty homogeneous floorcovering
- BRE Global environment A+ rating (Certificate No ENP 472)
- Achieves abrasion wear rating EN ISO 10581 Type I
- Polyurethane reinforcement to facilitate a low-cost, lifetime polish-free maintenance regime
- Sophisticated non-directional decoration with duotone base chips and marbled tonal highlight chips available in both sheet and tile
- Use Area Classification 23/34/43 as defined in EN 685




1260 Sunblaze 13.5



w/r 1260 NCS S 3560-Y80R

1250 Coral Drift 19.3




w/r 1250 NCS S 3050-Y80R

1230 Wild Mint 43.6



w/r 1230 NCS S 2020-B90G

1240 Cornbrook 52.4




w/r 1240 NCS S 1030-Y10R

1460 Shoreline 54.9



w/r 1460 NCS S 2020-Y30R

1320 Asparagus 37.3




w/r 8360 NCS S 2020-G40Y

1430 Silver Mist 61.8



w/r 1430 NCS S 1505-Y40R


1370 Satinwood 55.2



w/r 8320 NCS S 1505-Y30R




1220 Delta Blue 11.0




w/r 1220 NCS S 6020-R80B

1380 Nocturne 12.9




w/r 8270 NCS S 5005-R50B

1330 Mountain Lake 28.1




w/r 8350 NCS S 3020-R90B

1160 Smokestone 28.4




w/r 9120 NCS S 4502-G

1210 Cloudburst 31.8




w/r 1210 NCS S 2040-R90B

1200 Pale Slate 47.0




w/r 1200 NCS S 2005-B80G

1410 Ladoga 46.1




w/r 1410 NCS S 1515-R90B

1400 Quartz 50.3



w/r 9340 NCS S 2002-B

Please note: due to the limitations of printing, actual samples should be seen before colour selection is made. LRV Light Reflectance Value



Mystique PUR

Mystique PUR enables the transformation of any commercial environment with a bold array of colour.

Available in 12 bright colours, Mystique PUR features a stylish non-directional decoration, with a duotone chip decoration and three non-tonal highlight chips.



As with all Homogeneous PUR ranges, Mystique PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost polish-free maintenance regime for the lifetime of the flooring.

Polyflor Homogeneous PUR ranges demonstrate outstanding durability and abrasion resistance. Mystique PUR achieves the abrasion wear rating EN ISO 10581 Type I, demonstrating excellent resilience and long life.

Following an individual assessment from BRE Global, Mystique PUR achieves an A+ rating in major sectors such as health, education and retail (ENP 472).

Mystique PUR is 100% recyclable and contains 25% recycled material.

Ideally suited for heavy traffic areas, Mystique PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.




a vibrant collection

Mystique PUR


Duotone chip decoration with three non-tonal highlight chips

Key Features

- Attractive, high performance, heavy duty homogeneous floorcovering
- BRE Global environment A+ rating (Certificate No ENP 472)
- Achieves abrasion wear rating EN ISO 10581 Type I
- Polyurethane reinforcement to facilitate a low-cost, lifetime polish-free maintenance regime
- Vibrant non-directional decoration with duotone base chips and three tonal highlight chips available in both sheet and tile
- Use Area Classification 23/34/43 as defined in EN 685



3480 Bianco 65.0



w/r 3480 NCS S 1502-Y

3570 Azul 34.2




w/r 3570 NCS S 3030-R80B

3560 Beola 57.9




w/r 3560 NCS S 1505-Y40R

3520 Celeste 41.1




w/r 3520 NCS S 2030-R90B

3440 Ambra 47.7




w/r 1720 NCS S 2010-Y20R

3580 Giallo 47.2




w/r 3580 NCS S 1050-Y10R

3620 Alpi 42.8



w/r 3620 NCS S 2030-G10Y

3510 Azurite 11.5



w/r 1810 NCS S 4040-R90B

3500 Ametista 47.2



w/r 3500 NCS S 2030-Y40R

3460 Corallo 28.7




w/r 3460 NCS S 2040-Y50R

3600 Titanio 46.9



w/r 3600 NCS S 2502-B


3410 Grigio 25.6



w/r 3410 NCS S 4502-B



Please note: due to the limitations of printing, actual samples should be seen before colour selection is made. LRV Light Reflectance Value
All Mystique shades feature coloured highlight chips.



2000 PUR

2000 PUR, with its extensive proven pedigree, combines high performance with optimum style and enables the transformation of any commercial environment with a selection of bold, confident colours.

Available in 20 vibrant shades, 2000 PUR features a sophisticated directional duotone marbled decoration, with marbled highlight tones.

As with all Homogeneous PUR ranges, 2000 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost polish-free maintenance regime for the lifetime of the flooring.

Polyflor Homogeneous PUR ranges demonstrate outstanding durability and abrasion resistance. 2000 PUR achieves the abrasion wear rating Group M (EN 660 Part 2), EN ISO 10581 Type II, demonstrating excellent resilience and long life.

Following an individual assessment from BRE Global, 2000 PUR achieves an A+ rating in major sectors such as health, education and retail (ENP 472).

2000 PUR is 100% recyclable and contains 25% recycled material.

Ideally suited for heavy traffic areas, 2000 PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.



8450
Glacier Blue



8550
Sapphire



8350
Larkspur


a palette of opportunities

2000 PUR

Directional duotone marbled decoration with marbled highlight tones

Key Features

- Attractive, high performance, heavy duty homogeneous floorcovering
- BRE Global environment A+ rating (Certificate No ENP 472)
- Achieves abrasion wear rating Group M tested to EN 660 Part 2, as defined in EN 649, EN ISO 10581 Type II
- Polyurethane reinforcement to facilitate a low-cost, lifetime polish-free maintenance regime
- Vibrant duotone marbled decoration with marbled highlight tones
- Available in both sheet and tile and two gauges to suit differing traffic levels and locations
- Use Area Classification 23/34/43 as defined in EN 685




8800 Dawn Mist 60.0




w/r 8820 NCS S 2005-Y30R

8650 Wild Lilac 51.2



w/r 8650 NCS S 2005-R70B

8600 Thistle 18.2



w/r 8600 NCS S 4030-R70B

8500 Lace Blue 47.0



w/r 8500 NCS S 2502-Y

8300 Oak 54.1



w/r 8320 NCS S 2010-Y30R

8700 Mint Crest 44.8



w/r 8700 NCS S 2020-B60G

8450 Glacier Blue 42.4




w/r 8450 NCS S 2030-B

8050 Stream 35.0



w/r 8200 NCS S 3010-R90B

8950 Rosehip 36.8



w/r 8950 NCS S 3020-Y80R

8850 Buckwheat 39.2




w/r 8850 NCS S 3010-Y40R

8900 Blossom 51.5



w/r 8900 NCS S 1515-Y30R

8380 Willowbank 29.4



w/r 2120 NCS S 4010-B70G

8550 Sapphire 21.1




w/r 8550 NCS S 4030-R90B

8230 Stonewall 29.4



w/r 8230 NCS S 4502-B

8400 Sequoia 16.3



w/r 4120 NCS S 3040-Y80R

8000 Brushed Ochre 22.6



w/r 8000 NCS S 3050-Y70R

8490 Saffron 40.8



w/r 3070 NCS S 2050-Y20R

8750 Glenbeck 23.7




w/r 8750 NCS S 4030-B50G

8350 Larkspur 26.9




w/r 8350 NCS S 4020-R90B


8150 Shadow 12.1



w/r 8270 NCS S 7502-B



Please note: due to the limitations of printing, actual samples should be seen before colour selection is made. LRV Light Reflectance Value



Floorcare



Optimum Appearance

Appearance, hygiene and cleanliness are key points to consider when establishing a maintenance programme.

Poor maintenance can damage aesthetics, impairs performance, shortens floor life and creates hygiene problems in critical areas. In recognition of this Polyflor provides low maintenance options right across our product portfolio enabling the cleaning process to be as cost-effective and straightforward as possible.

The incorporation of a polyurethane reinforcement into the Polyflor Homogeneous PUR family of products, helps protect the floorcoverings by resisting soiling and scuffing. Combined with the superior closed surface finish, this enhanced protection allows the use of a polish-free maintenance regime for the lifetime of the flooring. Fewer cleaning chemicals and greatly reduced power requirements mean reduced environmental impact.

Where ease of maintenance and hygiene are important, Polyflor Homogeneous PUR sheet flooring may be taken up the wall, having created a radius using Polyflor Ejecta

accessories, including cove former and capping strip that gives a neat finish to the installation and ensures a continuous, sealed surface. The benefits of a sealed, easily maintained surface are invaluable in hospitals and other similar locations where hygiene is of paramount importance.

Welding rods are available for each Polyflor Homogeneous PUR shade to add the finishing touch and help to produce hygienic, continuous floors that offer no sanctuary to dirt and bacteria, as is often required in today's modern healthcare facilities for example.



Protection against infection

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection. Maintenance guidelines are available for all Homogeneous PUR ranges.

Resistance to chemicals

Polyflor Homogeneous PUR floorcoverings are suitable for use in all areas where most chemicals are used and there is only a risk of accidental spillage. Where specific chemicals are used, a set of chemical resistance charts is available on request. These charts show the resistance to a range of specific chemicals by shade for each Homogeneous PUR product, and will prove helpful in selecting colours which are least affected by specific chemicals.

Environmental Credentials



Environmental Credentials

All Polyflor ranges are launched with the greatest maintenance and environmental benefits built in and the Homogeneous PUR collection is no exception.

All Homogeneous PUR ranges have been individually assessed by BRE Global and have achieved the highest possible A+ rating, certificate no ENP 472 when used in major sectors such as healthcare, education and retail.

BRE's assessment is based on a life cycle analysis approach over a building life of 60 years, to ensure that products meet performance standards appropriate for their intended use. This independent assessment and certification can help the specifier sift through the various claims and counter claims that exist in the marketplace re environmental performance.

Polyflor also has individual and generic 3rd party Environmental Product Declarations, EN 15804 EPD, which are beneficial on BREEAM and LEED assessments. Globally recognised, EPDs offer transparent and consistent environmental data on a product's life cycle, including Polyflor Homogeneous PUR ranges.

Recycling

Polyflor has been recycling vinyl since the 1950's, when the company pioneered the manufacture of homogeneous flooring. It has always been considered a perfectly natural part of the manufacturing process.

All Polyflor Homogeneous PUR ranges are 100% recyclable. These ranges can in fact be recycled many times over without losing any of their performance properties and furthermore recycled vinyl requires 85% less energy to manufacture than virgin PVC.

All Polyflor Homogeneous PUR ranges contain an average 25% recycled material which is made up of both production and post consumer waste.

The Recofloor Scheme

It is important that we are responsible in the chain of custody of our products and we are proactively seeking to recover and recycle waste vinyl flooring for a closed-loop life cycle.

Polyflor is one of two founding and funding members of Recofloor, the unique industry vinyl flooring take-back scheme, which recycles post consumer smooth and safety

off-cuts back into new flooring and also recycles uplifted vinyl waste into other useful items such as traffic cones and road barrier bases.

As the involvement of distributors and contractors continues to increase, making recycling more accessible and efficient, more collection points and drop-off sites will be available and even less waste will go to landfill.




Technical Specifications

Product & Technical Information

Selecting a floorcovering that will satisfy the actual or expected service requirements is essential if a product is to perform up to the end user's expectations. With so much product information now available, it is hardly surprising that selection can sometimes be difficult.

The Polyflor Homogeneous PUR ranges, constructed from flexible PVC sheet and featuring a monolayer construction, i.e. one product throughout, for even wear and 100% useful life, set the bench-mark in terms of performance, quality and clarity of technical claims. This allows the end user to make a clear, informed choice when specifying a product range.


Bespoke Performance & Properties, Product Specifications and Maintenance instructions are available for all Homogeneous PUR ranges and these can be downloaded at www.polyflor.com.

| | | | PEARLAZZO PUR | PRESTIGE PUR | CLASSIC MYSTIQUE PUR | MYSTIQUE PUR | 2000 PUR |
|-------------------------------------|---|---|--|--|--|--|---|
| Gauge | EN 429 |  | 2.0mm – | 2.0mm – | 2.0mm – | 2.0mm – | 2.0mm 2.5mm |
| Roll Size | EN 426/427 |  | 2m x 20m = 40m ² – | 2m x 20m = 40m ² – | 2m x 20m = 40m ² – | 2m x 20m = 40m ² – | 2m x 20m = 40m ² 2m x 15m = 30m ² |
| Tile Size | EN 428 |  | – – | 300mm sq 608mm sq | 300mm sq 608mm sq | 300mm sq 608mm sq | 300mm sq 608mm sq |
| Product Weight | EN 430 |  | 2950g/m ² – | 2950g/m ² – | 3250g/m ² – | 3250g/m ² – | 3550g/m ² 4552g/m ² |
| General Performance | EN 649 ASTM F1913 ASTM F1700 |  | Conforms Conforms – | Conforms Conforms Conforms | Conforms Conforms Conforms | Conforms Conforms Conforms | Conforms Conforms Conforms |
| Agrément Assurance | Certificate No. |  | 94/3053 | 94/3053 | 94/3053 | 94/3053 | 94/3064 |
| Use Area Classification | EN 685 |  | 23, 34, 43 | 23, 34, 43 | 23, 34, 43 | 23, 34, 43 | 23, 34, 43 |
| Reaction to Fire | EN 13501-1 ASTM E662 ASTM E648 |  | Class Bfl-S1 <450 Class 1 | Class Bfl-S1 <450 Class 1 | Class Bfl-S1 <450 Class 1 | Class Bfl-S1 <450 Class 1 | Class Bfl-S1 <450 Class 1* |
| Slip Resistance | EN 13893 AS/NZS 4586 |  | Class DS R9 | Class DS R9 | Class DS R9 | Class DS R9 | Class DS R9 |
| Abrasion Resistance | EN 660 Part 2 EN ISO 10581 |  | Group T Type I | Group T Type I | – Type I | – Type I | Group M Type II |
| Indentation Residual | ASTM F970 (Modified) |  | 750psi | 750psi | 750psi | 750psi | 750psi |
| Castor Chair | EN 425 continuous use |  | Suitable | Suitable | Suitable | Suitable | Suitable |
| Electrical Behaviour | EN 1815 |  | <2kV | <2kV | <2kV | <2kV | <2kV |
| VOC Emissions | Indoor Air Comfort GOLD AgBB VOC test Floorscore certified Finnish M1 Classification Swedish B.P.D (FLEC test) GBCA/NZGBC Green Star IEQ-VOC |  | Certified Pass Reg No: SCS-FS-02034 Pass Best Class Compliant | Certified Pass Reg No: SCS-FS-02034 Pass Best Class Compliant | Certified Pass Reg No: SCS-FS-02034 Pass Best Class Compliant | Certified Pass Reg No: SCS-FS-02034 Pass Best Class Compliant | Certified Pass Reg No: SCS-FS-02034 Pass* Best Class Compliant |
| Environmentally Preferable Flooring | |  | BRE A+ ENP 472 100% Recyclable 25% Recycled material | BRE A+ ENP 472 100% Recyclable 25% Recycled material | BRE A+ ENP 472 100% Recyclable 25% Recycled material | BRE A+ ENP 472 100% Recyclable 25% Recycled material | BRE A+ ENP 472 100% Recyclable 25% Recycled material |
| Underfloor heating | Max 27°C |  | Suitable | Suitable | Suitable | Suitable | Suitable |
| Chemical resistance | EN 423 |  | Good | Good | Good | Good | Good |
| Light fastness | EN ISO 105-B02 |  | ≥6 | ≥6 | ≥6 | ≥6 | ≥6 |
| Hygiene | |  | + | + | + | + | + |
| Maintenance | |  | Polyurethane reinforcement | Polyurethane reinforcement | Polyurethane reinforcement | Polyurethane reinforcement | Polyurethane reinforcement |

+

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection. Maintenance guidelines are available for all Homogeneous PUR ranges.

* Certificate applies to 2.0mm gauge only.





POLYFLOR™ INTERNATIONAL

Australia

Polyflor Australia
Tel: +61 3 9215 4400
Tel: 1800 777 425
E-mail: sales@polyflor.com.au

Canada

Polyflor Canada Inc.
Tel: +1 905 364 3000
E-mail: sales@polyflor.ca

China

Polyflor Hong Kong
Tel: +(852) 2865 0101
E-mail: info@polyflor.com.hk

France

James Halstead France SAS
Tel: +33 (0) 8 20 20 32 11
E-mail: info@jhf.france.fr

Germany

objectflor Art und Design Belags GmbH
Tel: +49 (0) 2236 966 330
E-mail: info@objectflor.de

India

Polyflor India Pvt Ltd
Tel: +91 22 4476 4567
E-mail: info@polyflor.co.in

Ireland

Polyflor Ireland
Tel: +353 (1) 864 9304
E-mail: salesireland@polyflor.com

New Zealand

Polyflor New Zealand
Tel: +64 9 269 1111
Tel: 0800 765 935
E-mail: sales@polyflor.co.nz

Norway

Polyflor Nordic
Tel: +47 23 00 84 00
E-mail: firmapost@polyflor.no

Poland

Polflor Sp. z o.o.
Tel: +48 (0) 61 820 3155
E-mail: polyflor@polflor.com.pl

Russia

Polyflor Contract Ltd
Tel: +7 (812) 332 42 02
E-mail: info@polyflor.ru

South Africa

Poly Sales Africa (Pty.) Ltd
Tel: +27 11 609 3500
E-mail: info@polyflor.co.za

Sweden

FalckDesign AB
Tel: +46 (0) 300 15820
E-mail: info@falckdesign.com

United Arab Emirates

Poly Sales Tiles & Flooring Trading LLC
Tel: +971 4 349 1078
E-mail: dubai@polyflor.com

www.polyflor.com



POLYFLOR™ HEAD OFFICE

POLYFLOR LTD, PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK

UK SALES DIRECT: +44 (0)161 767 1122

UK SAMPLE REQUESTS: +44 (0)161 767 2551

EXPORT SALES DIRECT: +44 (0)161 767 1913

UK FAX: +44 (0)161 767 1128

EXPORT FAX: +44 (0)161 767 1166

TECHNICAL SUPPORT: +44 (0)161 767 1912

RECEPTION: +44 (0)161 767 1111

E-MAIL: INFO@POLYFLOR.COM

WEBSITE: WWW.POLYFLOR.COM